

DECLARATION OF PERFORMANCE AND CONFORMITY: EN 10088-4:2009

Document no.:

TEC-DOP-4016H

Revision 6

For the construction products: Hot Rolled Strip & Sheet of Corrosion Resisting Steel					
1.	Identification code of the product-type		1.4016 – EN 10088-4:2009		
2.	Туре		1.4016 See marking / label / inspection certificate		
3.	Intended use		Building Construction or Civil Engineering		
			Columbus Stainless (Pty) Ltd		
4.	Manufacturer	Hendrin		na Road, Middelburg, South Africa,	
			1050		
5.	Authorised Representative in the	ho Ell	Acerinox	ox Europa S.A.U. C/ Santiago de	
J.	·		Composteia n° 100. 28035 Madrid, Spain		
6.	Assessment system and verification for		EN 10088-4, Annex ZA, System 2+		
<u> </u>	constancy of performance as p	er Annex V			
	The Notified Body:		TÜV Rheinland Industrie Service GmbH, Koln		
	has conducted the first inspection and				
_	continuous surveillance according to the		2+ 0035-CPR-A304		
7.	system:				
	and issued the certificate:	for the feetens	0035-CP	R-A304	
	as a confirmation of conformity	for the factory			
Ω	Production control Construction product with European Technical Assessment: No				
	Construction product with European Technical Assessment: No Declared Performance:				
		D (
<u> </u>	Essential Characteristics	Performa	nce	Harmonised Technical Specification	
	Tolerances on Dimensions	Tables 1 to 10			
	Tolerances on Dimensions and Shape			Harmonised Technical Specification EN 10051:2010	
	Tolerances on Dimensions and Shape Mechanical Properties -	Tables 1 to 10			
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse:	Tables 1 to 10 Paragraphs 9,			
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength	Tables 1 to 10 Paragraphs 9, 450-600MPa		EN 10051:2010	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength	Tables 1 to 10 Paragraphs 9, 450-600MPa ≥260MPa			
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation	Tables 1 to 10 Paragraphs 9, 450-600MPa ≥260MPa ≥18%		EN 10051:2010	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength	Tables 1 to 10 Paragraphs 9, 450-600MPa ≥260MPa		EN 10051:2010	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by	Tables 1 to 10 Paragraphs 9, 450-600MPa ≥260MPa ≥18%		EN 10051:2010	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse:	Tables 1 to 10 Paragraphs 9, 450-600MPa ≥260MPa ≥18% N/A		EN 10051:2010 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by	Tables 1 to 10 Paragraphs 9, 450-600MPa ≥260MPa ≥18% N/A		EN 10051:2010 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition]	Tables 1 to 10 Paragraphs 9, 450-600MPa ≥260MPa ≥18% N/A Table 1		EN 10051:2010 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse:	Tables 1 to 10 Paragraphs 9, 450-600MPa ≥260MPa ≥18% N/A Table 1 Table 1		EN 10051:2010 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse:	Tables 1 to 10 Paragraphs 9, 450-600MPa ≥260MPa ≥18% N/A Table 1		EN 10051:2010 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1 to 10 Paragraphs 9, 450-600MPa ≥260MPa ≥18% N/A Table 1 Table 1 Table 7		EN 10051:2010 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact strength] Cold Formability [Covered by	Tables 1 to 10 Paragraphs 9, 450-600MPa ≥260MPa ≥18% N/A Table 1 Table 1		EN 10051:2010 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1 to 10 Paragraphs 9, 450-600MPa ≥260MPa ≥18% N/A Table 1 Table 1 Table 7	10 & 11	EN 10051:2010 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	

10. The performance of the product is in accordance with the specification given above. This Declaration of Performance is issued under the sole responsibility of Columbus Stainless (Pty) Ltd.

Signed for and on behalf of the manufacturer by:

NJ Fourie: Business Unit Manager Technical Signed at Middelburg, South Africa on the 12th day of June 2020