

## **DECLARATION OF PERFORMANCE AND CONFORMITY:** EN 10088-4:2009

Document no.:

TEC-DOP-4401H

Revision 7

For the construction products: Hot Rolled Strip & Sheet of Corrosion Resisting Steel					
1.				1.4401 – EN 10088-4:2009	
2.	Type		1.4401 See marking / label / inspection certificate		
3.	Intended use		Building Construction or Civil Engineering		
		Hendrin		ous Stainless (Pty) Ltd	
4.	Manufacturer			na Road, Middelburg, South Africa,	
			1050		
5.	Authorised Representative in the EU		Acerinox Europa S.A.U. C/ Santiago de Compostela nº 100. 28035 Madrid, Spain		
6.	Assessment system and verification for constancy of performance as per Annex V		EN 10088-4, Annex ZA, System 2+		
	The Notified Body:	70174111074 4	TÜV Rheinland Industrie Service GmbH, Koln		
	has conducted the first inspection and				
	continuous surveillance according to the		2+ 0035-CPR-A304		
7.	system:				
	and issued the certificate:				
	as a confirmation of conformity	for the factory			
	production control				
8.	Construction product with European Technical Assessment: No				
9.	9. Declared Performance:				
I I					
	<b>Essential Characteristics</b>	Performa	nce	Harmonised Technical Specification	
	Tolerances on Dimensions	Tables 1 to 10		Harmonised Technical Specification EN 10051:2010	
	Tolerances on Dimensions and Shape				
	Tolerances on Dimensions	Tables 1 to 10			
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:	Tables 1 to 10		EN 10051:2010	
	Tolerances on Dimensions and Shape  Mechanical Properties -	Tables 1 to 10 Paragraphs 9,			
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength	Tables 1 to 10 Paragraphs 9, 530-680MPa		EN 10051:2010	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength  • 0.2% Proof strength Elongation • Impact strength	Tables 1 to 10 Paragraphs 9, 530-680MPa ≥220MPa		EN 10051:2010	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength  • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by	Tables 1 to 10 Paragraphs 9, 530-680MPa ≥220MPa ≥40% ≥60J		EN 10051:2010  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition]	Tables 1 to 10 Paragraphs 9, 530-680MPa ≥220MPa ≥40%		EN 10051:2010	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength  • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by	Tables 1 to 10 Paragraphs 9,  530-680MPa ≥220MPa ≥40% ≥60J  Table 3		EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength  • 0.2% Proof strength  Elongation  • Impact strength  Weldability [Covered by chemical composition]  Durability [Covered by chemical composition]	Tables 1 to 10 Paragraphs 9, 530-680MPa ≥220MPa ≥40% ≥60J		EN 10051:2010  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:	Tables 1 to 10 Paragraphs 9,  530-680MPa ≥220MPa ≥40% ≥60J  Table 3  Table 3		EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact	Tables 1 to 10 Paragraphs 9,  530-680MPa ≥220MPa ≥40% ≥60J  Table 3		EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1 to 10 Paragraphs 9,  530-680MPa ≥220MPa ≥40% ≥60J  Table 3  Table 3  Table 10		EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact	Tables 1 to 10 Paragraphs 9,  530-680MPa ≥220MPa ≥40% ≥60J  Table 3  Table 3		EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009	

10. The performance of the product is in accordance with the specification given above. This Declaration of Performance is issued under the sole responsibility of Columbus Stainless (Pty) Ltd.

Signed for and on behalf of the manufacturer by:

NJ Fourie: Business Unit Manager Technical Signed at Middelburg, South Africa on the 12<sup>th</sup> day of June 2020