

DECLARATION OF PERFORMANCE AND CONFORMITY: EN 10088-4:2009

Document no.:

TEC-DOP-4509C

Revision 5

For the construction products: Cold Rolled Strip & Sheet of Corrosion Resisting Steel					
1.				1.4509 – EN 10088-4:2009	
2.	Туре		1.4509 See marking / label / inspection certificate		
3.	Intended use		Building Construction or Civil Engineering		
		Columbus Stainless (Pty) Ltd			
4.	Manufacturer			na Road, Middelburg, South Africa,	
			1050		
5.	Authorised Representative in the EU		Acerinox Europa S.A.U. C/ Santiago de Compostela nº 100. 28035 Madrid, Spain		
	Assessment system and verific	cation for			
6.	6. constancy of performance as per Annex		EN 10088-4, Annex ZA, System 2+		
	The Notified Body:		TÜV Rheinland Industrie Service GmbH, Koln		
	has conducted the first inspection and				
II _	continuous surveillance according to the		2+ 0035-CPR-A304		
7.	system:				
	and issued the certificate: as a confirmation of conformity for the factory				
	production control	for the factory			
8.	Construction product with European Technical Assessment: No				
	Declared Performance:				
		Performance			
I I	Essential Characteristics	Performs	nco	Harmonised Technical Specification	
	Essential Characteristics			Harmonised Technical Specification	
	Tolerances on Dimensions	Tables 1, 2, 3	& 4	Harmonised Technical Specification ISO 9445-2:2009	
	Tolerances on Dimensions and Shape		& 4	-	
	Tolerances on Dimensions and Shape Mechanical Properties -	Tables 1, 2, 3	& 4	-	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse:	Tables 1, 2, 3 o Paragraphs 11	& 4	ISO 9445-2:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength	Tables 1, 2, 3	& 4	-	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength	Tables 1, 2, 3 of Paragraphs 11	& 4	ISO 9445-2:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength	Tables 1, 2, 3 of Paragraphs 11 430-630MPa ≥250MPa	& 4	ISO 9445-2:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation	Tables 1, 2, 3 of Paragraphs 11 430-630MPa ≥250MPa ≥18% N/A	& 4	ISO 9445-2:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition]	Tables 1, 2, 3 of Paragraphs 11 430-630MPa ≥250MPa ≥18%	& 4	ISO 9445-2:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by	Tables 1, 2, 3 of Paragraphs 11 430-630MPa ≥250MPa ≥18% N/A Table 1	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition]	Tables 1, 2, 3 of Paragraphs 11 430-630MPa ≥250MPa ≥18% N/A	& 4	ISO 9445-2:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse:	Tables 1, 2, 3 of Paragraphs 11 430-630MPa ≥250MPa ≥18% N/A Table 1 Table 1	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse:	Tables 1, 2, 3 of Paragraphs 11 430-630MPa ≥250MPa ≥18% N/A Table 1	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1, 2, 3 of Paragraphs 11 430-630MPa ≥250MPa ≥18% N/A Table 1 Table 1 Table 7	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact strength] Cold Formability [Covered by	Tables 1, 2, 3 of Paragraphs 11 430-630MPa ≥250MPa ≥18% N/A Table 1 Table 1	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1, 2, 3 of Paragraphs 11 430-630MPa ≥250MPa ≥18% N/A Table 1 Table 1 Table 7	& 4 , 12 & 13	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	

10. The performance of the product is in accordance with the specification given above. This Declaration of Performance is issued under the sole responsibility of Columbus Stainless (Pty) Ltd.

Signed for and on behalf of the manufacturer by:

NJ Fourie: Business Unit Manager Technical Signed at Middelburg, South Africa on the 12th day of June 2020