

## **DECLARATION OF PERFORMANCE AND CONFORMITY:** EN 10088-4:2009

Document no.:

TEC-DOP-4512H

Revision 6

For the construction products: Hot Rolled Strip & Sheet of Corrosion Resisting Steel					
1.	Identification code of the produ	ıct-type	1.4512 – EN 10088-4:2009		
2.	Type		1.4512 See marking / label / inspection certificate		
3.	Intended use		Building Construction or Civil Engineering		
		Columbus Stainless (Pty) Ltd Hendrina Road, Middelburg, South Africa,			
4.	Manufacturer			na Road, Middelburg, South Africa,	
ll .			1050		
5.	Authorised Representative in the	ho Ell	Acerinox	ox Europa S.A.U. C/ Santiago de	
J.	•	Compo		ostela nº 100. 28035 Madrid, Spain	
6.	Assessment system and verific		EN 10088-4, Annex ZA, System 2+		
U.	constancy of performance as per Annex V				
ll .	The Notified Body:		TÜV Rheinland Industrie Service GmbH, Koln		
	has conducted the first inspection and				
	continuous surveillance according to the		2+ 0035-CPR-A304		
7.	system:				
ll .	and issued the certificate:	for the feetens	0035-CP	R-A304	
	as a confirmation of conformity	for the factory			
8.	Construction product with European Technical Assessment: No				
9.					
l I					
	Essential Characteristics	Performa	ince	Harmonised Technical Specification	
	Tolerances on Dimensions	Tables 1 to 10			
	Tolerances on Dimensions and Shape			Harmonised Technical Specification EN 10051:2010	
	Tolerances on Dimensions and Shape  Mechanical Properties -	Tables 1 to 10		•	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:	Tables 1 to 10 Paragraphs 9,		•	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength	Tables 1 to 10 Paragraphs 9, 380-560MPa		EN 10051:2010	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength	Tables 1 to 10 Paragraphs 9, 380-560MPa ≥220MPa		•	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation	Tables 1 to 10 Paragraphs 9, 380-560MPa ≥220MPa ≥25%		EN 10051:2010	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength  • 0.2% Proof strength Elongation • Impact strength	Tables 1 to 10 Paragraphs 9, 380-560MPa ≥220MPa		EN 10051:2010	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength  • 0.2% Proof strength Elongation • Impact strength  Weldability [Covered by	Tables 1 to 10 Paragraphs 9, 380-560MPa ≥220MPa ≥25%		EN 10051:2010	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:	Tables 1 to 10 Paragraphs 9, 380-560MPa ≥220MPa ≥25% N/A		EN 10051:2010  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by	Tables 1 to 10 Paragraphs 9, 380-560MPa ≥220MPa ≥25% N/A		EN 10051:2010  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength  • 0.2% Proof strength Elongation • Impact strength  Weldability [Covered by chemical composition]  Durability [Covered by chemical composition]	Tables 1 to 10 Paragraphs 9,  380-560MPa ≥220MPa ≥25% N/A Table 1		EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:	Tables 1 to 10 Paragraphs 9,  380-560MPa ≥220MPa ≥25% N/A  Table 1  Table 1		EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:	Tables 1 to 10 Paragraphs 9,  380-560MPa ≥220MPa ≥25% N/A Table 1		EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength  Weldability [Covered by chemical composition]  Durability [Covered by chemical composition]  Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1 to 10 Paragraphs 9,  380-560MPa ≥220MPa ≥25% N/A  Table 1  Table 1  Table 7		EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength  • 0.2% Proof strength Elongation • Impact strength  Weldability [Covered by chemical composition]  Durability [Covered by chemical composition]  Fracture Toughness / Brittle Strength [Covered by impact strength]  Cold Formability [Covered by	Tables 1 to 10 Paragraphs 9,  380-560MPa ≥220MPa ≥25% N/A  Table 1  Table 1		EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength  Weldability [Covered by chemical composition]  Durability [Covered by chemical composition]  Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1 to 10 Paragraphs 9,  380-560MPa ≥220MPa ≥25% N/A  Table 1  Table 1  Table 7	10 & 11	EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009	

10. The performance of the product is in accordance with the specification given above. This Declaration of Performance is issued under the sole responsibility of Columbus Stainless (Pty) Ltd.

Signed for and on behalf of the manufacturer by:

NJ Fourie: Business Unit Manager Technical Signed at Middelburg, South Africa on the 12<sup>th</sup> day of June 2020