

## DECLARATION OF PERFORMANCE AND CONFORMITY: EN 10088-4:2009

Document no.:

TEC-DOP-4526C

**Revision 6** 

For the construction products: Cold Rolled Strip & Sheet of Corrosion Resisting Steel						
	1.Identification code of the product-type1.4526 – EN 10088-4:2009					
2			ot type	1.4526 See marking / label / inspection certificate		
3		ed use		Building Construction or Civil Engineering		
				Columbus Stainless (Pty) Ltd		
4	I. Manufa	Manufacturer		Hendrina Road, Middelburg, South Africa,		
				1050		
		Authorized Depresents they in the EU		Acerinox Europa S.A.U. C/ Santiago de		
5	5. Authorised Representative in th		Compos		stela nº 100. 28035 Madrid, Spain	
6		ment system and verific		EN 10088-4, Annex ZA, System 2+		
	consta	ncy of performance as p	er Annex V			
		The Notified Body:			TÜV Rheinland Industrie Service GmbH, Koln	
		has conducted the first inspection and				
1 -		continuous surveillance according to the		2+ 0035-CPR-A304		
11 '	,	system: and issued the certificate:				
			for the factory	0000-01		
	as a confirmation of conformity for production control		for the factory			
8	<ul> <li>B. Construction product with European Technical</li> </ul>			Assessment: No		
9. Declared Performance:						
	Essential Characteristics					
	Essent	ial Characteristics	Performa	ince	Harmonised Technical Specification	n
┣	Tolerar	nces on Dimensions	Tables 1, 2, 3	& 4		n
	Tolerar and Sh	nces on Dimensions ape		& 4	Harmonised Technical Specification	n
	Tolerar and Sh Mecha	nces on Dimensions ape nical Properties -	Tables 1, 2, 3	& 4		n
	Tolerar and Sh Mecha Transv	nces on Dimensions ape nical Properties - erse:	Tables 1, 2, 3 Paragraphs 11	& 4		n
	Tolerar and Sh Mecha Transv	nces on Dimensions ape nical Properties - erse: Tensile strength	Tables 1, 2, 3 Paragraphs 11 480-560MPa	& 4		n
	Tolerar and Sh Mecha Transv	nces on Dimensions ape nical Properties - erse: Tensile strength 0.2% Proof strength	Tables 1, 2, 3 Paragraphs 11 480-560MPa ≥300MPa	& 4	ISO 9445-2:2009	n
	Tolerar and Sh Mecha Transv •	nces on Dimensions ape nical Properties - erse: Tensile strength 0.2% Proof strength Elongation	Tables 1, 2, 3 √ Paragraphs 11 480-560MPa ≥300MPa ≥25%	& 4	ISO 9445-2:2009	n
	Tolerar and Sh Mecha Transv •	nces on Dimensions hape nical Properties - erse: Tensile strength 0.2% Proof strength Elongation Impact strength	Tables 1, 2, 3 √ Paragraphs 11 480-560MPa ≥300MPa ≥25% N/A	& 4	ISO 9445-2:2009 EN 10088-4:2009	n
	Tolerar and Sh Mecha Transv • • • •	nces on Dimensions ape nical Properties - erse: Tensile strength 0.2% Proof strength Elongation	Tables 1, 2, 3 √ Paragraphs 11 480-560MPa ≥300MPa ≥25%	& 4	ISO 9445-2:2009	n
	Tolerar and Sh Mecha Transv • • • Weldat chemic	nces on Dimensions ape nical Properties - erse: Tensile strength 0.2% Proof strength Elongation Impact strength Dility [Covered by	Tables 1, 2, 3 4 Paragraphs 11 480-560MPa ≥300MPa ≥25% N/A Table 1	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009	n 
	Tolerar and Sh Mecha Transv • • • • Weldat chemic Durabil chemic	nces on Dimensions ape nical Properties - erse: Tensile strength 0.2% Proof strength Elongation Impact strength bility [Covered by cal composition] ity [Covered by cal composition]	Tables 1, 2, 3 √ Paragraphs 11 480-560MPa ≥300MPa ≥25% N/A	& 4	ISO 9445-2:2009 EN 10088-4:2009	n
	Tolerar and Sh Mecha Transv • • • Weldat chemic Durabil chemic Fractur	nces on Dimensions ape nical Properties - erse: Tensile strength 0.2% Proof strength Elongation Impact strength bility [Covered by cal composition] ity [Covered by cal composition] re Toughness / Brittle	Tables 1, 2, 3 √ Paragraphs 11 480-560MPa ≥300MPa ≥25% N/A Table 1 Table 1	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	n 
	Tolerar and Sh Mecha Transv • • • • • • • • • • • • • • • • • • •	nces on Dimensions hape nical Properties - erse: Tensile strength 0.2% Proof strength Elongation Impact strength bility [Covered by cal composition] hity [Covered by cal composition] re Toughness / Brittle th [Covered by impact	Tables 1, 2, 3 4 Paragraphs 11 480-560MPa ≥300MPa ≥25% N/A Table 1	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009	n 
	Tolerar and Sh Mecha Transv • • • Weldat chemic Durabil chemic Fractur Strengt strengt	nces on Dimensions hape nical Properties - erse: Tensile strength 0.2% Proof strength Elongation Impact strength bility [Covered by cal composition] ity [Covered by cal composition] re Toughness / Brittle th [Covered by impact h]	Tables 1, 2, 3 √ Paragraphs 11 480-560MPa ≥300MPa ≥25% N/A Table 1 Table 1	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	n 
	Tolerar and Sh Mecha Transv • • • • • • • • • • • • • • • • • • •	nces on Dimensions ape nical Properties - erse: Tensile strength 0.2% Proof strength Elongation Impact strength Dility [Covered by cal composition] ity [Covered by cal composition] re Toughness / Brittle th [Covered by impact h] ormability [Covered by	Tables 1, 2, 3 √ Paragraphs 11 480-560MPa ≥300MPa ≥25% N/A Table 1 Table 1	& 4	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	n 
	Tolerar and Sh Mecha Transv • • • • • • • • • • • • • • • • • • •	nces on Dimensions ape nical Properties - erse: Tensile strength 0.2% Proof strength Elongation Impact strength Dility [Covered by cal composition] ity [Covered by cal composition] re Toughness / Brittle th [Covered by impact h] ormability [Covered by	Tables 1, 2, 3 ↔ Paragraphs 11 480-560MPa ≥300MPa ≥25% N/A Table 1 Table 1 Table 7	& 4 , 12 & 13	ISO 9445-2:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	n 

10. The performance of the product is in accordance with the specification given above.

This Declaration of Performance is issued under the sole responsibility of Columbus Stainless (Pty) Ltd.

Signed for and on behalf of the manufacturer by:

NJ Fourie: Business Unit Manager Technical Signed at Middelburg, South Africa on the 12<sup>th</sup> day of June 2020