

DECLARATION OF PERFORMANCE AND CONFORMITY: EN 10088-4:2009

Document no.:

TEC-DOP-4541H

Revision 7

For the construction products: Hot Rolled Strip & Sheet of Corrosion Resisting Steel					
1.	Identification code of the produ	ıct-type	1.4541 – EN 10088-4:2009		
2.	Type		1.4541 See marking / label / inspection certificate		
3.	Intended use		Building Construction or Civil Engineering		
		Columbus Stainless (Pty) Ltd		us Stainless (Pty) Ltd	
4.	Manufacturer		Hendrina Road, Middelburg, South Africa,		
			1050		
l -	Authorized Donnes autotive in t	ь - Г. I	Acerinox Europa S.A.U. C/ Santiago de		
5.	Authorised Representative in t	Compos		stela nº 100. 28035 Madrid, Spain	
6.	Assessment system and verification for		EN 10088-4, Annex ZA, System 2+		
0.	constancy of performance as per Annex V				
	The Notified Body:		TÜV Rheinland Industrie Service GmbH, Koln		
	has conducted the first inspect				
	continuous surveillance according to the		2+ 0035-CPR-A304		
7.	system:				
	and issued the certificate:		0035-CP	R-A304	
	as a confirmation of conformity	for the factory			
	production control Construction product with Furnace Technical Assessment: No.				
8. 9.	Construction product with European Technical Assessment: No Declared Performance:				
	Essential Characteristics	Performa	ance	Harmonised Technical Specification	
╟	Tolerances on Dimensions	Tables 1 to 10		-	
	Tolerances on Dimensions and Shape			Harmonised Technical Specification EN 10051:2010	
	Tolerances on Dimensions and Shape Mechanical Properties -	Tables 1 to 10		-	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse:	Tables 1 to 10 Paragraphs 9,		-	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength	Tables 1 to 10 Paragraphs 9, 520-720MPa		EN 10051:2010	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength	Tables 1 to 10 Paragraphs 9, 520-720MPa ≥200MPa		-	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation	Tables 1 to 10 Paragraphs 9, 520-720MPa ≥200MPa ≥40%		EN 10051:2010	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength	Tables 1 to 10 Paragraphs 9, 520-720MPa ≥200MPa		EN 10051:2010	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by	Tables 1 to 10 Paragraphs 9, 520-720MPa ≥200MPa ≥40%		EN 10051:2010	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition]	Tables 1 to 10 Paragraphs 9, 520-720MPa ≥200MPa ≥40% ≥60J		EN 10051:2010 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by	Tables 1 to 10 Paragraphs 9, 520-720MPa ≥200MPa ≥40% ≥60J		EN 10051:2010 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition]	Tables 1 to 10 Paragraphs 9, 520-720MPa ≥200MPa ≥40% ≥60J Table 3		EN 10051:2010 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle	Tables 1 to 10 Paragraphs 9, 520-720MPa ≥200MPa ≥40% ≥60J Table 3 Table 3		EN 10051:2010 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact	Tables 1 to 10 Paragraphs 9, 520-720MPa ≥200MPa ≥40% ≥60J Table 3		EN 10051:2010 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1 to 10 Paragraphs 9, 520-720MPa ≥200MPa ≥40% ≥60J Table 3 Table 3 Table 10		EN 10051:2010 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact strength] Cold Formability [Covered by	Tables 1 to 10 Paragraphs 9, 520-720MPa ≥200MPa ≥40% ≥60J Table 3 Table 3		EN 10051:2010 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1 to 10 Paragraphs 9, 520-720MPa ≥200MPa ≥40% ≥60J Table 3 Table 3 Table 10	10 & 11	EN 10051:2010 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	

10. The performance of the product is in accordance with the specification given above. This Declaration of Performance is issued under the sole responsibility of Columbus Stainless (Pty) Ltd.

Signed for and on behalf of the manufacturer by:

NJ Fourie: Business Unit Manager Technical Signed at Middelburg, South Africa on the 12th day of June 2020