

DECLARATION OF PERFORMANCE AND CONFORMITY: EN 10088-4:2009

Document no.:

TEC-DOP-4571H

Revision 7

For the construction products: Hot Rolled Strip & Sheet of Corrosion Resisting Steel					
1.				1.4571 – EN 10088-4:2009	
2.	Type		1.4571 See marking / label / inspection certificate		
3.	Intended use		Building Construction or Civil Engineering		
		Columbus Stainless (Pty) Ltd Hendrina Road, Middelburg, South Africa,			
4.	Manufacturer			na Road, Middelburg, South Africa,	
			1050		
5.	Authorised Representative in the	ho Ell	Acerinox	ox Europa S.A.U. C/ Santiago de	
J.	•	Compo		postela nº 100. 28035 Madrid, Spain	
6.	Assessment system and verification for		EN 10088-4, Annex ZA, System 2+		
U.	constancy of performance as per Annex V				
	The Notified Body:		TÜV Rheinland Industrie Service GmbH, Koln		
	has conducted the first inspection and				
	continuous surveillance according to the		2+ 0035-CPR-A304		
7.	system:				
	and issued the certificate:	. fo the o fo oto	0035-CP	R-A304	
	as a confirmation of conformity	for the factory			
-	Construction product with European Technical Assessment: No				
8. 9.					
	Casautial Characteristics				
	Essential Characteristics	Performa	nce	Harmonised Technical Specification	
	Tolerances on Dimensions	Tables 1 to 10		•	
	Tolerances on Dimensions and Shape			Harmonised Technical Specification EN 10051:2010	
	Tolerances on Dimensions and Shape Mechanical Properties -	Tables 1 to 10		•	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse:	Tables 1 to 10 Paragraphs 9,		•	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength	Tables 1 to 10 Paragraphs 9, 540-690MPa		EN 10051:2010	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength	Tables 1 to 10 Paragraphs 9, 540-690MPa ≥220MPa		•	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation	Tables 1 to 10 Paragraphs 9, 540-690MPa ≥220MPa ≥40%		EN 10051:2010	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength	Tables 1 to 10 Paragraphs 9, 540-690MPa ≥220MPa		EN 10051:2010	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by	Tables 1 to 10 Paragraphs 9, 540-690MPa ≥220MPa ≥40%		EN 10051:2010	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse:	Tables 1 to 10 Paragraphs 9, 540-690MPa ≥220MPa ≥40% ≥60J		EN 10051:2010 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by	Tables 1 to 10 Paragraphs 9, 540-690MPa ≥220MPa ≥40% ≥60J		EN 10051:2010 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition]	Tables 1 to 10 Paragraphs 9, 540-690MPa ≥220MPa ≥40% ≥60J Table 3		EN 10051:2010 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse:	Tables 1 to 10 Paragraphs 9, 540-690MPa ≥220MPa ≥40% ≥60J Table 3 Table 3		EN 10051:2010 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse:	Tables 1 to 10 Paragraphs 9, 540-690MPa ≥220MPa ≥40% ≥60J Table 3		EN 10051:2010 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1 to 10 Paragraphs 9, 540-690MPa ≥220MPa ≥40% ≥60J Table 3 Table 3 Table 10		EN 10051:2010 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact strength] Cold Formability [Covered by	Tables 1 to 10 Paragraphs 9, 540-690MPa ≥220MPa ≥40% ≥60J Table 3 Table 3		EN 10051:2010 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse: • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1 to 10 Paragraphs 9, 540-690MPa ≥220MPa ≥40% ≥60J Table 3 Table 3 Table 10	10 & 11	EN 10051:2010 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009 EN 10088-4:2009	

10. The performance of the product is in accordance with the specification given above. This Declaration of Performance is issued under the sole responsibility of Columbus Stainless (Pty) Ltd.

Signed for and on behalf of the manufacturer by:

NJ Fourie: Business Unit Manager Technical Signed at Middelburg, South Africa on the 12th day of June 2020